

# SDR-65 / SDR-90 Roller Finishing Mower

### High Performance - Full Featured

The Progressive **SDR-65** and **SDR-90** are a three point hitch versions of the popular tri-deck TDR-15 and TDR-22 mowers and they utilize many of the same components. Not to be confused with other, light duty three point hitch mowers that are available, both the **SDR-65** and **SDR-90** have 6" diameter rollers on both the front and rear across the full width of the deck. Ideal for smaller mowing jobs where a quality cut is mandatory, the **SDR's** rollers allow you to cut as low as ½", while simultaneously striping and rolling the mowing surface. To minimize service requirements, both models are equipped with field proven maintenance free blade spindles and roller-end bearings.

If a new mower is in your plans to maintain your sports complex, park or other areas where a quality after cut appearance is mandatory, consider the 65 inch wide **SDR-65**. If a wider cutting swath for a seed bed or small test plot is required, consider the 90 inch wide **SDR-90**.

Progressive's **SDR** mowers are another example of the ingenuity and quality that goes in to producing durable, reliable rotary finishing mowers that are easy to maintain. They are "*The Better Built Choice*".



## Single Deck Roller

### SDR-65 / SDR-90 Roller Finishing Mowers

#### Easy height adjustment:

Infinite cutting height adjustment from ½" to 4".

Using the supplied tool the mower cutting height can be adjusted quickly for multiple mowing applications. The SDR-90 can be fitted with either one piece fixed blades or the replaceable tip Pro-Ez II blade system

## Full width rollers:

Each 6" diameter, thick wall rollers with 'Hex' shaft ends is supported by two 1¼" ductile iron flange bearings. A cable wiper is position by each roller to eliminate grass build-up in damp mowing conditions.

#### **Heavy duty lift link:**

Designed with a standardized Cat 1, 3 point lift linkage Reinforced, heavy duty mounting points on the mower deck for long life. (may need weights on front of tractor)

#### <u>Simpler Maintenance = Lower Cost:</u>

Maintenance Free Blade Spindles and sealed rollerend bearings are used to lower both the cost and time spent on routine maintenace. They also provide peace of mind that a missed daily greasing won't render the mower out of service.







**SDR-90** 

## **SDR Roller Finishing Mower Specifications**

Part Number: 531965 531990 **Cutting Width:** 65 inches 90 inches Blades: 3 x 23 inches long 4 x 24 inches long ½" to 4" ½" to 4" **Cutting Height:** (infinite number of settings) 1.25 acres / hour 1.8 acres / hour Mowing Capacity: 2 mph 4 mph 2.5 acres / hour 3.56 acres / hour 6 mph 3.75 acres / hour 5.33 acres / hour **Recommended PTO HP:** 25 HP 35HP **Transport Width:** 72 inches 92 inches Weight: 975 lbs 1380 lbs.

**SDR-65** 

Under our policy of continuous improvement, we reserve the right to change specifications and designs without prior notice. The illustrations shown do not necessarily represent the standard version of product offered by Progressive Turf Equipment Inc.

(800) 668-8873 (519) 527-1080 FAX: (519) 527-2275 www.progressiveturfequip.com info@progressiveturfequip.com

